

Rebar Spacer Specifications

WHEELCHAIRS

Features	7/8"	1"	1" LC	1 1/2"	2"	3"	Stackable Chair	Bolster
Locking				x	x	x	Interstack	x
Non-Locking	x	x	x	x	x	x		
Total Coverage	7/8"	1"	1"	1 1/2"	2"	3"	1.5-2"	1" - 3"
Minimum Wall Size	2"	2.4"	2.75" - 3"	3.75"	4.5"	6.25"		
Rebar Sizes	Wire - #3	Wire - #3	#3-#6	#3-#7	#3-#7	#3-#7	#3-#8	Any Size
Maximum Weight	400	400	400	600	600	600	400	200
Material	HDPE	HDPE	HDPE	HDPE	HDPE	Polycarb	ABS	ABS
Available Sand Pad							x	

LOCKING WHEEL CHAIRS

Features	1"	1 1/2"	2"	3"
Total Coverage	1"	1 1/2"	2"	3"
Minimum Wall Size	2.75"	3.75"	4.5"	6.25"
Rebar Sizes	Wire - #4	#3-#6	#3-#7	#3-#8
Maximum Weight	400	600	600	600
Material	HDPE	HDPE	HDPE	Polycarb

PUSH ON WHEEL CHAIRS

Features	7/8"	1"	1" LC	1 1/2"	2"	3"
Total Coverage	7/8"	1"	1"	1 1/2"	2"	3"
Minimum Wall Size	2"	2.4"	2.75" - 3"	3.75"	4.5"	6.25"
Rebar Sizes	Wire - #3	Wire - #3	#3-#6	#3-#6	#3-#6	#3-#6
Maximum Weight	400	400	400	150	150	150
Material	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE

STACKABLE CHAIRS AND ROUND BASE CHAIRS

Features	Stackable Chair	Round Base Chair
Total Coverage	1.5-2"	2.5-3"
Rebar Sizes	Wire - #8	Wire - #8
Maximum Weight	400	300
Material	ABS	ABS
Available Sand Pad	x	Attached

SLAB BOLSTERS BY HEIGHT

Features	3/4"	1"	1 1/4"	1 1/2"	1 3/4"	2"	2 1/4"	2 1/2"	2 3/4"	3"
Stackable	x	x	x	x	x	x	x	x	x	x
20" Length		x		x		x		x		x
44" Length	x	x	x	x	x	x	x	x	x	x
Rebar Sizes	Any Size	Any Size	Any Size	Any Size	Any Size	Any Size	Any Size	Any Size	Any Size	Any Size
Maximum Weight	300	300	300	300	300	300	300	300	300	300
Material	Polycarb	Polycarb	Polycarb	Polycarb	Polycarb	Polycarb	Polycarb	Polycarb	Polycarb	Polycarb

Polylok, Inc.
3 Fairfield Blvd.
Wallingford, CT 06492
1-877-765-9565
www.polylok.com