

Effluent Filter Station

The all-in-one Effluent Filter Station offers effective wastewater filtration in one assembled unit

The Polylok Effluent Filter Station offers a 'connect and go', highly effective, filtration solution that upgrades existing tanks with 1.6mm filtration. A fully assembled solution when existing tanks are inaccessible for filter installation. Simply add after the tank and before distribution of wastewater.



To find out more:

email sales@polylok.eu or

call - +353 (0)59 86 31524

Typical Applications:

1. Installation at outlet of a new or existing septic tank
2. Installation at outlet of a new or existing wastewater treatment plant

Main Benefits:

1. Includes PL-122 Filter with Integrated ball
2. Easy to install, just 'Connect & Go'!
3. Prevents solids entering the percolation area or drainage field
4. Filtration up to 1.6mm
5. Suitable for maximum daily flows up to 5700 litres/day
6. Easy cleaning and maintenance.
7. Green, lockable 600mm dome cover with integrated handles
8. Polylok risers can be added to the station to increase the height to finish at ground level if required
9. Available in 5 pre-assembled sizes



Five Pre-Assembled Sizes:

1.5m high	(425ltr)	SKU: 1.5MSTEPS
1.35m high	(380ltr)	SKU: 1.35MSTEPS
1.2m high	(340ltr)	SKU: 1.2MSTEPS
1.05m high	(295ltr)	SKU: 1.05MSTEPS
0.9m high	(255ltr)	SKU: 0.9MSTEPS